

# Low level order pickers

**ECE 220 / 225** 

Lift height: 125 mm / Load capacity: 2000-2500 kg





### The solid basis

# for maximum picking performance.

#### Sturdy construction for tough applications.

Our flexible and efficient series 2 low level order pickers combine highest picking performance with optimum energy efficiency and first-class driving comfort. Offering various operating levels, these vehicles cover individual storage requirements without the slightest effort. Working with the ECE means optimised picking processes with maximum performance.

Picking comfortably, safely and without delay: Particularly high battery capacities guarantee highest picking rates, even in economic multi-shift operations. The sturdy construction and compact dimensions allow easy cornering with fast acceleration. Furthermore, a cushioned, adjustable stand-on platform protects against impact.

The spacious driver's seat with height-adjustable jetPILOT multifunction steering wheel and easy to reach controls provide high riding comfort. Assistance systems such as the dayLED daytime running lights, floor spot or the optional curveCONTROL ensure the necessary safety.



#### No worries. No compromise.

With the Jungheinrich Li-ion Guarantee Plus, we give you a long-term performance promise of up to 8 years on our high-quality lithium-ion batteries, so you can completely concentrate on your tasks without worrying.



#### 100% satisfaction. Guaranteed.

We are convinced our lithium-ion technology is right for you. That's why we guarantee that you can easily and quickly switch back to the technology you originally used at any time within the first 6 months after delivery.

#### All benefits at a glance

- Optimum picking performance with low energy consumption
- · Powerful motor with high acceleration
- jetPILOT for intuitive operation same as driving a car
- · Extensive options for an optimal workplace
- Semi-automatic remote control easyPILOT (optional)

<sup>\*</sup> In accordance with our warranty terms - see website for details.

# Your Jungheinrich order picker

### for maximum customer benefits.



#### **Efficiency**

# Maximum performance with the most efficient trucks.

Our horizontal order pickers impress with lowest energy consumption and highest throughput coupled with perfect riding comfort.

#### Powerful and efficient drive concept

- Powerful acceleration and high top speed.
- Optional drivePLUS package with highly efficient 3.2 kW motor for even greater drive and acceleration performance.
- Safe cornering speed thanks to load-dependent curveCONTROL (optional).
- Optional drive&ecoPLUS package for additional energy saving.

### Flexible switching between different control options

- Long distances (from approx. 10 m): Travelling with jetPILOT.
- Medium distances: Remote operation with Jungheinrich easyPILOT allows for full focus on the picking process.
- Short distances: Positioning at the correct pallet and fine adjustment, e.g. via touch mode on the backrest (optional).

### Available with lithium-ion technology

- High availability thanks to extremely short charging times.
- No battery exchange required.
- Saving costs due to longer service life and low maintenance in comparison with lead-acid batteries.
- No charging rooms and ventilation required as there is no build-up of gas.



#### Safety

## Best prerequisites for working safely.

Always keeping track for sovereign picking: A central display instrument, various driving programs and EasyAccess control make this possible.

### Rugged construction for the toughest applications

- Impact-protected drive panel and raised frame apron made from high-quality steel.
- Torsion-resistant load forks with draw bar kinematics prevent distortion, even with heavy loads and long support arms.
- 2.5 t for the transport of up to 3 pallets simultaneously.

### Hydraulically lifting stand-on platform (HP)

- For frequent order picking from the second racking level (optional).
- Rapid and safe raising of the operator up to the height of the battery panel.
- Operation of platform via foot pedal, leaving hands free for order picking.
- The optional jetPILOT can be raised together with the platform (HP-LJ), allowing the truck to be positioned even when the platform is raised.

## Central display and clear instruments for complete overview

- Activation of the truck by EasyAccess via softkey, PIN code or optional transponder card.
- The 2-inch display provides information on the battery discharge status, number of operating hours, travel speed as well as error codes.
- Selection from three travel programs via softkey (optional).



#### **Individuality**

# A forklift truck as individual as your business.

More driving safety and driving pleasure – the jetPILOT multifunction steering wheel is not only awardwinning, it also offers secure grip in every situation.

### Perfect workstation for maximum picking performance

- Various, individually adjustable storage options.
- Additional cushioned and movable stand-on platform (optional).
- Quick lifting of the load through optional double actuation of the lifting button.

#### jetPILOT multifunction steering wheel

- Intuitive and comfortable operation, similar to a car, with safe and secure grip.
- Reduced strain on neck and spinal column when cornering.
- One-handed operation and automatic return of the steering wheel to straight line travel.
- Adjustable to individual body size.

#### Additional optional equipment

- A comprehensive range of accessories allows for individual tailoring to your requirements.
- Additional accessories for working at the second racking level.
- Sturdy, universally applicable options bracket, e.g. for radio data transmission components.
- Increased ease of use with optional sprung stand-on platform to reduce the vibrations felt by the operator.

# **Overview**

## The right solution for your applications:

Name	Load capacity/load	Travel speed unladen	Aisle width (pallet 800x1200 length)	Lift speed unladen
ECE 220	2000 kg	12.5 km/h	2670 mm	0.1 m/s
ECE 220 HP	2000 kg	12.5 km/h	2820 mm	0.1 m/s
ECE 225	2500 kg	12.5 km/h	3870 mm	0.1 m/s
ECE 225 HP	2500 kg	12.5 km/h	4020 mm	0.1 m/s

The German production facilities in Norderstedt, Moosburg and Landsberg are certified.





